

LIMELITE HERITAGE LIME GROUT



PRODUCT DATA SHEET

LIMELITE CANAL GROUT

LIMELITE HERITAGE PRODUCTS

LIMELITE CANAL GROUT

Description

Limelite Canal Grout is a high yield bentonite based grout designed for use in canal walls, sealing foundations, tunnels, vaults and manholes from water.

Features

- One component mix
- Factory blended
- Low strength
- Good pumping characteristics
- Sets to a clay putty consistency
- Does not migrate

Application

The typical water to powder ratio is 3:1. Suitable mixing equipment includes bougee pan, paddle mixer and colloidal mixer. Suitable pumping equipment includes helical screw, diaphragm and piston types. Water for mixing **Limelite Canal Grout** should be clean and comply with requirements of BS EN 1008 (as for making of concrete).

Packaging and Storage

Limelite Canal Grout is available in nominal 20kg sacks, palletised and shrink wrapped.

Palletised **Limelite Canal Grout** should be stored in cool dry areas clear of the ground, sheeted or under cover and stacked not more than two pallets high.

The product should be used on a first in – first out basis.

Shelf life is minimum 3 months when properly stored but could be in excess of 6 months subject to temperature and humidity conditions.

Quality Control

All Limelite products are factory blended, tested and packaged to quality control procedures in accordance with BS EN ISO 9001.

Clean Up and Spilages

Dry powders should be swept up and disposed of in accordance with the local authority regulations.



Health & Safety

Health and safety advice, which must be followed, can be found on the Material Safety Data Sheet.

Users are advised to wear face mask, goggles, gloves and overalls when handling, mixing and applying cementitious products.

Contains Portland Cement Contains Chromium (VI), which may produce an allergic reaction. Clothing contaminated by wet cement should be removed immediately and washed before reuse. R38 - Irritating to skin. R41 - Risk to serious damage to eyes. S26 - In case of contact with eyes, rinse immediately with water and seek medical advice. S37/39 - Wear suitable gloves and eye/face protection. S2 - Keep out of reach of children.

Information, Prices & Ordering

If you have any questions about choosing the right product for your particular job, or if you are ready to order, please call us on:

03444 63 00 46

Tarmac Building Products Ltd

Swains Park Industrial Estate, Park Road, Swadlincote, Overseal, Derbyshire, DE12 6JT

Tel: 03444 63 00 46

Email: limelite@tarmacbp.co.uk

Web: www.limeliteheritage.co.uk

The information supplied in our literature or given by our employees is based upon extensive knowledge and experience. This information, together with that supplied by our agents or distributors, is given in good faith in order to help you. Our Company policy is one of continuous Research and Development; we therefore reserve the right to update this information at any time without prior notice. We also guarantee the consistent high quality of our products; however, as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. Any existing intellectual property right must be observed. Tarmac's standard terms and conditions apply.